

A COMPLETELY NEW, AFFORDABLE CYTOLOGY CENTRIFUGE



Removable, sealed rotor

Process up to six
specimens simultaneously

Digital controls



FEATURES

- Removable, sealed rotor
- Processes up to 6 specimens at one time
- Digital controls with LCD display:
 - Stores up to 25 programs for instant recall
 - Programmed speeds from 250 – 2400 rpm
 - Displays the programmed and remaining run time from 1-99 minutes
 - 3 acceleration options allows flexibility and protection for fragile samples
- Audible alarms:
 - Signals the SlidePrep Plus is out of balance
 - Alarm reminds users at 1 minute intervals to remove specimens to protect them from air-drying and to ensure consistent results
- Safety:
 - Load and unload the sealed head in a biological safety cabinet
 - Operates only when the lid is locked into position
 - Auto-locking, plastic outer lid
 - Lid remains locked at all times during rotation
 - Sealed head is autoclavable
- 2 year warranty

PRODUCT SPECIFICATIONS

- Maximum capacity: Six filled cytology funnels
- Brushless motor
- Temperature range: Operating 10°C (50°F) - 40°C (104°F). Storage -10°C (14°F) - 60°C (140°F)
- Dimensions: 254 (w) x 382 (d) x 254 mm (h)
- Operating noise level: Less than 65 db
- Weight: 4.5kg

FULL SIZE **POWER AND FEATURES** IN A SMALL-SIZE PACKAGE

The SlidePrep Plus™ is perfect for use in cytology, microbiology, hematology/oncology, virology, veterinary laboratories, research/general laboratories, and FISH testing.

Slide Prep Plus™

Catalog No.	Description
100-400	SlidePrep Plus Centrifuge, 120V/60HZ • U.S. Configuration
100-401	SlidePrep Plus Centrifuge, 230V/50HZ • Europe Configuration
100-404	SlidePrep Plus Centrifuge, 120V/60HZ • Central/South America Configuration



Distributed by

Manufacturer

Separation Technology, Inc.
570 Monroe Road, Suite 1000,
Sanford, FL 32771
Tel. +1 407 788 8791

Sales

EKF Diagnostics Holdings plc
Avon House, 19 Stanwell Road,
Penarth, Cardiff, UK, CF64 2EZ
Tel. +44 (0)29 20 710570
www.ekfdiagnostics.com

